



## START AUXILIARY (STARTING FLUID)

Vistony® Starting Aid is a special additive with a high concentration of Ether that is able to run engines when low temperature or humidity conditions prevent the engine from starting cold. Saves cranking time, battery and cylinder wear.

### USES

It is designed to be used in engines of:

2 and 4 stroke gasoline.

Diesel without glow plugs.

Also applicable in industrial motors (lawnmowers, leaf blowers, chain saws, etc.). Do not use in motors with electric air heaters.

### PROPERTIES

- It ensures the cold start of diesel, gasoline, and dual engines (NGV and LPG).
- Reduces wear on the ignition system.
- Increases the life of the accumulator.
- Contains lubricants, anti-corrosion and anti-wear

### HOW TO USE

With the engine previously off, spray the Starting Aid into the engine intake air system or carburetor for a brief period of 2 to 3 seconds, then immediately start the engine until a stable gear is obtained. Gasoline engines: accelerate slightly. Diesel engines: start at idle. Do not use preheaters.

### HEALTH AND SAFETY

Wear glasses, in case of contact with eyes, skin, wash with plenty of water. If irritation persists, consult a doctor. In case of ingestion, do not induce vomiting and require urgent medical attention. Do not expose to heat, puncture or incinerate the container. Highly flammable product.

### AVAILABLE SIZES

START AUXILIARY
10 Oz. Spray / 296 ml.

### TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	AVERAGE VALUES
Specific gravity		0.713
Boiling point	°F	-49
Melting point	°F	-117
Evaporation Radius		37.5
Water solubility		Mild
Appearance and Color	Visual	Colorless / Odor ether