



RADIATOR CLEANING SOLUTION

Concentrated additive formulated to remove existing impurities in the radiator and the entire engine cooling system. It forms a protective layer that prevents the formation of new oxides, sediment, and scales, extending the useful life of the cooling system. It increases the power of the motor and allows the free circulation of water at an ideal temperature.

USES

- In all types of diesel and gasoline engine cooling systems.
- Pour the contents of the container into the radiator and fill it with water up to its level, start the engine and keep it accelerated for 10 minutes so that the product is ready to activate its remover action.
- Then drain the system completely (block, radiator, etc.).
- Then wash the system with water until it runs clear.
- For better results when washing the radiator, add Antioxidant and / or VISTONY Coolant / Antifreeze (1 L) and combine with water (preferably VISTONY battery water) until the tank is full.

PROPERTIES

- Removes rust, grease residues and mud.
- Helps prevent overheating of the cooling system by keeping it free of impurities and dirt.
- Does not damage metal or radiator parts.
- Prevents radiator breakage (leaks).
- Safe for all types of system.
- Fast action.
- Neutralizer is not needed.

HEALTH AND SAFETY

This product does not present a health or safety risk as long as good personal and industrial hygiene practices are maintained. In case of contact with the skin, wash. Do not pour the residue on plants. Take care of our environment.

AVAILABLE SIZES

RADIATOR CLEANING SOLUTION

300 ml can.

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	AVERAGE VALUES
Color	Brown
Emulsion stability, 5% v / v in hard water	24 h. Minimum
emulsion pH	7.5 – 8.5